

09-05-00

A

Docket No. CGTES.0143

Patent

jc912 U.S. PTO
09/01/00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Stephen Paul Brennan and James Ralph Bradford**Title:** Method and Apparatus for Determining the Carrier Used for an AIN Call**Docket No.:** CGTES.0143jc564 U.S. PTO
09/05/00
09/01/00

TRANSMITTAL

Assistant Commissioner for Patents
BOX PATENT APPLICATION
Washington, D.C. 20231

Attached for filing in the United States Patent and Trademark Office is the patent application identified above, comprising:

1. Declaration and Power of Attorney
2. Specification containing 29 pages, claims and abstract
3. 4 sheets of drawings including 4 Figures
4. Express Mail Certificate
5. Postcard Acknowledgement

The filing fee has been computed as follows:

Basic Fee		\$690.00
Additional Fees:		
26	Total number of claims (whether independent or dependent) in excess of 20, times \$18.00	\$108.00
6	Number of independent claims, Minus 3, times \$78.00	\$234.00
TOTAL:		\$1,032.00


09-05-00

A check for \$1,032.00 is enclosed. Please charge any additional amounts required to Deposit Account No. 50-0392. A duplicate copy of this letter is submitted.

In the event the Examiner wishes to contact attorneys of record concerning the merits of the accompanying application prior to the first Office Action, such contact should be made with the undersigned attorney.

Respectfully submitted,

Date: Sept. 1, 2000

By: 
David W. Carstens

CARSTENS, YEE & CAHOON, L.L. P.
P.O. Box 802334
Dallas, TX 75380
972.367.2001 Telephone
972.367.2002 Facsimile

001060-11115960

CERTIFICATE OF MAILING BY EXPRESS MAIL

I hereby certify that the documents listed below are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service, Mail Label No. EL555422673US, addressed to the Assistant Commission for Patents, BOX PATENT APPLICATION, Washington, D.C. 20231, under 37 CFR 1.10, on September 1, 2000.

Kathleen A. Tolnay

Enclosures:

Transmittal letter (original and one copy)

Check payable to the Assistant Commissioner for Patents
in the amount of \$1,032.00

Declaration and Power of Attorney

Specification containing 29 pages, claims and abstract

4 sheets of drawings including 4 Figures

Express Mail Certificate

Postcard Acknowledgement

Docket No. CGTES.0143

APPLICATION FOR
UNITED STATES LETTERS PATENT

FOR
METHOD AND APPARATUS FOR DETERMINING THE
CARRIER USED FOR AN AIN CALL

By:

Stephen Paul Brennan and James Ralph Bradford

Certificate under 37 CFR 1.10 of Mailing by "Express Mail"

EL555422673US

"Express Mail" label number

September 1, 2000

Date of Deposit

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the BOX PATENT APPLICATION, Assistant Commissioner for Patents, Washington, D.C. 20231.

Kathleen A. Tolnay

Signature of person mailing correspondence

Kathleen A. Tolnay

Typed or printed name of person mailing correspondence

BACKGROUND OF THE INVENTION

1. Technical Field:

5 The present invention relates to telecommunication services, and more particularly to a method and apparatus for routing an advanced intelligence network call to the appropriate carrier for call completion.

2. Description of the Related Art:

10 In recent years, a number of new service features have been provided by an enhanced telephone network which has come to be called an Advanced Intelligent Network (AIN). In an AIN type system, local and/or toll offices of the public telephone network can detect one of a number of call processing events which are identified as AIN
15 “triggers.” For an ordinary telephone service call there is no event that triggers AIN processing, and the local and toll office switches would function normally and process such calls without referring to the AIN database for instructions. When a central office detects a trigger, the call is suspended and a call data message is forwarded via a common channel inter-office signaling (CCIS) link to a service control point which includes a
20 multi-services application platform (MSAP) database. If additional information is needed, the SCP can instruct the central office to obtain and forward additional information. Once sufficient information regarding the call has reached the SCP, the SCP accesses its stored data tables in the MSAP database to translate the received call data message into a call control message and then return the call control message to the central
25 office via the CCIS link. The central office then uses the call control message to complete the particular call.

 Recently, legislative and regulatory changes require the local exchange carrier (LEC) to unbundle certain network elements and services and offer use of those elements

and services to other carriers for resale to end users. These changes have resulted in the necessity for more complex routing of telephone calls because more than one carrier can provide local and long distance service in any given geographic area. The introduction of multiple carriers into this market has resulted in greater complexity for AIN service logic programs in determining how an AIN call should be routed. The current AIN service logic does not have means for determining whether a call should be routed by the LEC, the IntraLATA carrier, or the InterLATA carrier. This has resulted in customer complaints regarding erroneous billing for calls that were misrouted using current methods. Thus, there is a need for a method and apparatus for determining whether the carrier that is required for a particular AIN is the local exchange carrier (LEC), the Intra-LATA carrier, or the Inter-LATA carrier.

SUMMARY OF THE INVENTION

The present invention provides a method for determining the carrier that should be used for a particular AIN call. The following information is derived for each call: the originating calling party number, the terminating called party number, the originating LATA, and the terminating LATA. Using these components, pre-defined tables are accessed that contain local calling plan information. These tables contain rate center and dial plan information that provides the local calling scope that is available to the originator of the call. Based on the information contained in the tables, the appropriate type of carrier for the call is selected and the call is routed using this carrier.

BRIEF DESCRIPTION OF THE DRAWINGS

Figures 1 and 2 are collectively a flow chart in accordance with an embodiment of the invention.

Figure 3 is a hypothetical LATA Table in accordance with an embodiment of the invention.

Figure 4 is a hypothetical Originating Rate Center Table in accordance with an embodiment of the invention.

DETAILED DESCRIPTION

Advanced Intelligent Network (AIN) services are becoming more and more popular. To process an AIN call, the AIN service logic programs (SLP) must be able to determine when a call should be routed using LEC facilities, IntraLATA facilities or InterLATA facilities. The AIN-equipped CO is also commonly referred to as a service switching point (SSP). SSPs are appropriately equipped programmable switches present in the telephone network which recognize AIN type calls, launch queries to the AIN Service Control Point (SCP) and receive commands and data from the AIN SCP to further process the AIN calls. Various triggers may be programmed into the SSP which perform a query to the SCP when an AIN call is made. When the SCP receives a query, the AIN service logic program (SLP) is invoked for the particular service associated with the trigger that caused the query. Once the processing associated with that particular AIN service is complete, the SLP instructs the SSP to provide call termination information and to complete the call. The SSP then completes the AIN call.

Because the caller or "originator" of an AIN call may not necessarily be a local caller due to the fact that AIN calls are not routed like a normal call, the SLP contains special logic that determines the local calling scope of the caller. Using this information, the SLP determines which type of carrier is the appropriate carrier for the call. The special logic detects the appropriate carrier for the call by referring to tables that identify the rate center according to the first six digits of the telephone number. For instance, the first six digits, e.g. 972-718 (the NPA-NXX combination) for the telephone number 972-718-9999, indicate which telephone company's franchise and the central office that serve the calling party. However, the first seven digits, e.g. 972-718-9 (the NPA-NXX-X combination), of the telephone number may be required where 1K Number Pooling is being used. 1K Number Pooling is simply a means for transferring telephone numbers to another telephone company franchise or central office within the same rate center. For

example, all of the numbers beginning with 972-718-9 could be assigned to telephone company franchise A, and all of the other numbers beginning with 972-718 could be assigned to telephone company franchise B. Each NPA-NXX (or NPA-NXX-X as the case may be) combination within a Local Access and Transport Area (LATA) are defined in tables referred to herein as LATA tables. The LATA tables may be stored in the MSAP database. The rate center assigned to each NPA-NXX or NPA-NXX-X (when applicable) is defined in the LATA table which is described in greater detail in reference to **Figure 3**. A rate center is a uniquely defined geographical area within an exchange area used for determining mileage measurements for the application of interstate tariffs.

Referring now to **Figures 1 and 2**, a flow chart of an embodiment of the invention is illustrated. When an AIN call is made to an SSP, a query is launched by the SSP serving the call to the SCP, thereby invoking a service logic program (SLP). A carrier determination module within this service logic program determines how a particular AIN call should be routed. **Figures 1 and 2** represent the logical flow of the carrier determination module for determining which type of carrier should be used for routing the call, whether it be the Local Exchange Carrier (LEC), the IntraLATA carrier, or the InterLATA carrier. Before this module is invoked by the SLP, the originating telephone number and the terminating telephone number are collected from the SSP by the SCP. The originating and terminating LATA's are determined based on the originating and terminating NPA-NXX, respectively. The AIN SLP will not use this information until a determination has been made that this is not a local call. After the carrier determination module is invoked (step **105**), the originating NPA-NXX is compared with the terminating NPA-NXX. If these numbers are equivalent, then the primary carrier for the call is set to the local exchange carrier. The reason for this is that when the NPA-NXX are equivalent for both the originating number and the terminating number, then by definition, the call is a local call and should be routed by the local exchange carrier. Thus, the program exits (step **120**) and the SCP instructs the SSP to route the call using

the local exchange carrier.

If the originating NPA-NXX and the terminating NPA-NXX are not the same at step 110, then a search of the LATA Table is performed to determine whether the originating NPA-NXX-X and an associated rate center are in the LATA Table (step 125). This search will only be successful when 1K Number Pooling is being used with the originating rate center. If the search is unsuccessful, then a search is made to determine whether the originating NPA-NXX and an associated rate center are in the LATA Table (step 130). If the originating NPA-NXX and rate center are also not found in the LATA Table, then an error is logged (step 135) because a matching record was not found in the LATA Table. Such an error may occur if the LATA table is not available or if the rate center for the associated NPA-NXX code is not provisioned in the LATA table.

When a matching record for the originating NPA-NXX is not found in the LATA Table at step 130, the originating LATA is compared to the terminating LATA (step 140). If the originating LATA, i.e. the LATA within which the call originated, is equal to the terminating LATA, i.e. the LATA within which the call is terminated, then the primary carrier is set to the local exchange carrier (step 150) and the module exits (step 120). However, if the originating LATA is not equal to the terminating LATA at step 140, then the primary carrier is set to the InterLATA carrier that is assigned to the customer with the AIN trigger that resulted in the service logic program being invoked (step 145). The IntraLATA carrier for the customer is derived from the Call Processing Record (CPR) for the AIN customer, i.e. the database that contains information regarding the customer with AIN service, and the module exits (step 120).

If the originating NPA-NXX-X and rate center are found in the LATA Table at step 125 or if the originating NPA-NXX and rate center are found in the LATA Table at step 130, then a determination is made as to whether the terminating NPA-NXX-X and rate center are found in the LATA Table (step 155). If the terminating NPA-NXX-X and rate center are not found in the LATA Table at step 155, then a query is made to

determine if the terminating NPA-NXX and rate center are found in the LATA Table (step 160). If the terminating NPA-NXX-X/NPA-NXX and associated rate center cannot be located in the identified LATA Table or if the LATA Table does not exist then an error is logged (step 165).

5 When a matching record for the terminating NPA-NXX is not found in the LATA Table at step 160, the originating LATA is compared to the terminating LATA (step 140) using LATA information that is passed to the service logic program. If the originating LATA is the same as the terminating LATA, then the primary carrier is set to the local exchange carrier (step 150) and the module exits (step 120). However, if the originating LATA is not equal to the terminating LATA at step 140, then the primary carrier is set to the InterLATA carrier that is assigned customer with the AIN trigger that resulted in the service logic program being invoked (step 145). The InterLATA carrier is derived from the Call Processing Record (CPR) for the AIN customer. Then the module exits (step 120).

10 If the terminating NPA-NXX-X/NPA-NXX and associated rate center are found at step 155 or step 160, then the rate center in the LATA Table for the originating NPA-NXX or NPA-NXX-X is compared to the rate center in the LATA Table for the terminating NPA-NXX or NPA-NXX-X (step 170). If the rate centers are the same, then the primary carrier is set to the local exchange carrier (step 175) and the module exits (step 120). However, if the originating rate center is not the same as the terminating rate center at step 170, then a search is made to determine if the Originating Rate Center Table for the originator is available (step 180). The Originating Rate Center Table is a table containing information specific to that rate center such as the terminating rate centers within the local calling scope of that originating rate center. This table is described in greater detail below in reference to **Figure 4**. If no Originating Rate Center Table is available at step 180, then an error message is logged (step 185).

 If an Originating Rate Center Table is not found at step 180, the originating

LATA value is compared with the terminating LATA value (step 140). If the originating LATA is the same as the terminating LATA, then the primary carrier is set to the local exchange carrier (step 150) and the module exits (step 120). However, if the originating LATA is not equal to the terminating LATA at step 140, then the primary carrier is set to the InterLATA carrier that is assigned to the AIN customer (step 145). This information is derived from the Call Processing Record (CPR) for the AIN customer. Then the module exits (step 120).

However, if an Originating Rate Center Table for the originator is found at step 180, then a search for the terminating rate center within the Originating Rate Center Table is made (step 205). All rate centers to which a local call may be made from the originating rate center are identified in the Originating Rate Center Table as defined below in reference to **Figure 4**. If the terminating rate center is not found within the Originating Rate Center Table (step 210), then the originating LATA value is compared with the terminating LATA value (step 270). If the originating and terminating LATA values are equal, then the primary carrier value is set to the IntraLATA carrier assigned to the AIN customer if an IntraLATA carrier has been assigned or to the local exchange carrier if an IntraLATA carrier has not been assigned (step 280). The local exchange carrier is the default IntraLATA carrier unless the customer has specified another carrier for IntraLATA toll calls. The module then exits (step 120). If the originating and terminating LATAs are not the same at step 270, then the primary carrier value is set to the InterLATA carrier for the AIN customer (step 275) and the module exits (step 120).

If the terminating rate center is found in the Originating Rate Center Table at step 210, then a check of the Originating Rate Center Table is made to determine whether there are any dial plans associated with the terminating rate center (step 215). If there are no dial plans associated with the terminating rate center, i.e. the dial plan entries in the Originating Rate Center Table are null for that particular terminating rate center, then the primary carrier is set to the local exchange carrier (step 220) and the module exits (step

120). However, if the dial plan entries are not null at step 215, this means that the dial plan must be in effect for the call to be a local one. First, a determination is made as to whether the dial plan associated with the terminating rate center is an Extended Metro Service (EMS). If the dial plan associated with the terminating rate center is not an EMS at step 225, then it is determined whether an optional dial plan is assigned to the originator (step 230). If there is an optional dial plan assigned to the originator at step 230, then a comparison of the originator's optional plan to the Originating Rate Center Table optional dial plan value assigned to the applicable terminating rate center is made (step 235). If the optional dial plan value assigned to the applicable terminating rate center matches the optional dial plan for the originating rate center (step 240), then the primary carrier is set to the local exchange carrier (step 245) and the module exits 120. However, if no matching optional dial plan is found at step 240 or if there is no optional dial plan assigned to the originator at step 230, then the originating LATA value is compared to the terminating LATA value (step 270). If the originating and terminating LATA values are equal, then the primary carrier value is set to the IntraLATA carrier assigned to the AIN customer if an IntraLATA carrier has been assigned or to the local exchange carrier if an IntraLATA carrier has not been assigned (step 280). The module then exits (step 120). If the originating and terminating LATAs are not the same at step 270, then the primary carrier value is set to the InterLATA carrier for the AIN customer (step 275) and the module exits (step 120).

In the event that the dial plan entry in the Originating Rate Center Table for the terminating rate center is EMS at step 225, then the dial plan for the originating NPA-NXX or NPA-NXX-X (as the case may be) in the LATA Table is checked to determine if the dial plan for the originator is EMS (step 250). If the originating NPA-NXX/NPA-NXX-X dial plan is EMS then the primary carrier is set to the local exchange carrier (step 255) and the module exits (step 120). If the originating NPA-NXX/NPA-NXX-X dial plan is not EMS at step 250, then the dial plan for the terminating NPA-NXX/NPA-

NXX-X is checked in the LATA table (step 260). If the terminating NPA-NXX/NPA-NXX-X dial plan in the terminating LATA Table is EMS at step 260, then the primary carrier is set to the local exchange carrier (step 265) and the module exits (step 120). Thus, if the dial plan in the Originating Rate Center Table associated with the terminating rate center is EMS, the call will always be a local call if either the originator or the called party has the EMS option.

However, if neither the originating number nor the terminating number have an EMS dial plan at step 260, then a comparison between the originating LATA value and the terminating LATA value is made (step 270). If the originating and terminating LATA values are equal, then the primary carrier value is set to the IntraLATA carrier assigned to the AIN customer if an IntraLATA carrier has been assigned or to the local exchange carrier if an IntraLATA carrier has not been assigned (step 280). The module then exits (step 120). If the originating and terminating LATAs are not the same at step 270, then the primary carrier value is set to the InterLATA carrier for the AIN customer (step 275) and the module exits (step 120).

Referring now to **Figure 3**, an example of a LATA Table in accordance with the present invention is illustrated. This table is only illustrative of the table structure and is presented only for demonstration purposes. The actual data that would be inserted into the LATA Table must correspond with the actual values in existence. For example, one embodiment of the invention has a LATA Table which contains information regarding the North American Numbering Plan (NANP) in this table and each LATA within the NANP is defined. The service logic program will then use the originating/terminating LATA as a key to retrieve information from this table. If a matching LATA record cannot be found, the service logic will log an error as described above in reference to **Figures 1 and 2**. The Table shown in **Figure 3** is only a portion of the LATA Table that would actually be implemented in practice. For a plan that covers the United States or North America, the LATA Table would be very large and would contain information

regarding every single LATA. However, in **Figure 3**, only the LATA designated by the key number 552 is illustrated.

The LATA Table may be stored as an array in the SCP storage device such as in the MSAP database. The table is searchable by the LATA key and the NPA-NXX or NPA-NXX-X key. The LATA Table is divided into several columns. The first column is a LATA (key) identifier column **305** which has numerical identifiers that indicate which LATA a particular NPA-NXX/NPA-NXX-X is associated with. Each NPA-NXX combination within a LATA is also defined in the NPA-NXX or NPA-NXX-X column **310**. To support 1K number pooling, the NPA-NXX combination must be expandable down to the thousandth level (NPA-NXX-X).

The service logic program used to retrieve information from this table performs the initial search based on the NPA-NXX-X values as described above in reference to **Figure 1**. If a record cannot be found, the service logic will perform a subsequent search using the NPA-NXX value. The third column is the rate center column **315**. The rate center assigned to each NPA-NXX or NPA-NXX-X (when applicable) combination must be defined in this table. For example, entry **325** in the LATA Table has NPA-NXX key of 817264 and is within the Arlington rate center.

Column four of the LATA Table is the dial plan column **320** which contains information regarding the Dial Plan for each NPA-NXX combination. For example, the 817264 combination in the Arlington rate center has the EMS dial plan. This dial plan, called the Extended Metro Service (EMS) plan, is used in the Dallas/Fort Worth and Houston, Texas metropolitan areas and offers extended two-way local calling capabilities. All qualifying EMS calls are routed by the local exchange carrier. These numbers are also commonly referred to as "Metro" numbers.

Column five of the LATA Table is the Central Office Code (COC) type column **330**. The COC type for each NPA-NXX/NPA-NXX-X combination may be defined in this table to provide additional information concerning the NPA-NXX or NPA-NXX-X

combination that can be used by AIN service logic programs. A COC type is a three-position field defining the Central Office Code. For example, the COC type could be EOC which is the End Office Code. The COC type could also be PMC which refers to Public Mobile Carrier. Numerous other types of Central Office Codes may be used or
5 implemented into the LATA Table without departing from the scope or spirit of the invention.

Column six of the LATA Table is the Originating Company Number (OCN)
column **335**. The OCN for each NPA-NXX or NPA-NXX-X combination must be defined. The OCN will provide additional information concerning the NPA-NXX or
10 NPA-NXX-X that could be used by the AIN service logic programs. The four-position alphanumeric field is a simplified method for identifying an NPA-NXX or NPA-NXX-X code holder, switching entity, company, and non-facility based service provider such as resellers and billing service providers.

Referring now to **Figure 4**, an example of an Originating Rate Center Table in
15 accordance with the present invention is illustrated. In one embodiment, The Originating Rate Center Table contains the information specific to each rate center within the LATA where AIN services are provided. The Originating Rate Center Table provides existing and future AIN service logic programs with the information needed to determine when the call should be routed by the local exchange carrier. The table of **Figure 4** illustrates a
20 table in which one single table is used to define all of the rate centers within one LATA. The table of **Figure 4** only illustrates or gives information for a portion of the originating rate centers within the hypothetical 552 LATA. The LATA key column **405** is used to index the originating rate center within an individual LATA. The LATA Table of **Figure 4** is an example that illustrates what a LATA Table for the Grapevine originating rate
25 center would look like. The Originating Rate Center column **410** can also be used as a key to search the table.

Column three of the Originating Rate Center Table is the Terminating Rate Center

column 415. Each terminating rate center that is within the local, extended area service, or extended local calling scope of the identifying originating rate center is recorded in this table. This information is then used to determine when the local exchange carrier should route the call. For example, the Grapevine originating rate center contains 31 different terminating rate centers starting with Allen and ending with Weatherford. The number of terminating rate centers that are within the local, extended area service, or extended local calling scope of an identified originating rate center determines the number of entries in this table for a particular originating rate center.

The Originating Rate Center Table also contains a column to indicate whether a particular dial plan is associated with the terminating rate center. Column four of the Originating Rate Center Table is the Dial Plan column 420. The dial plan associated with the terminating rate center is used to instruct the service logic program to use the dial plan associated with the originating and/or terminating NPA-NXX/NPA-NXX-X that is defined in the LATA Table of Figure 3. In the Dial Plan column 420, the Extended Metro Service (EMS) dial plan is implemented. The entry in the Dial Plan column 420 is populated with "EMS" if an originating or terminating EMS code is required to complete the call on a local basis.

Columns five, six, seven and eight of Figure 4 allow for the assignment of optional dial plans to each terminating rate center. Local service providers may offer originating based extended local calling plans. In this embodiment, up to four different optional dial plans can be assigned to each terminating rate center using the originating Rate Center Table of Figure 4. AIN customers who have an optional dial plan will have a unique identifier positioned within their AIN call processing record (CPR). The applicable AIN service logic compares this optional dial plan identifier associated with the CPR to the optional dial plan that is assigned to the terminating rate center, if any. If a match is found, then the service logic will route the call using the local exchange carrier.

Referring to the table entries of **Figure 3** and **Figure 4**, an illustration of the operation of the invention may be made. If a call is made from an NPA-NXX number "817251" to a terminating NPA-NXX number of "817307," then the LATA Table will be searched and it will be determined that both of these NPA-NXX numbers are contained within the LATA Table at rows **340** and **345**, respectively. The Originating Rate Center Table for the 552 LATA will be accessed in **Figure 4** to determine that there is an Originating Rate Center Table for the Grapevine originating rate center. A search is made of all of the rows having Grapevine as an originating rate center to determine if the Arlington Rate Center is listed as a terminating rate center. A search of the table of **Figure 4** indicates that Arlington is indeed listed as a terminating rate center for Grapevine at row **425**. However, the Dial Plan column is populated with "EMS." Thus, in order to route the call as a local call, either the originating NPA-NXX number or the terminating NPA-NXX number must have an EMS dial plan in the LATA Table of **Figure 3**. However, neither "817251" nor "817307" have an extended dial plan. Therefore, the next question is whether the originating LATA is the same as the terminating LATA. In this case, both the originating LATA and the terminating LATA is "552" and therefore the primary carrier is set to the IntraLATA carrier for the AIN customer. If there is no IntraLATA carrier assigned, then the local exchange carrier is used to route the call. If the call had been made to a "817272" number in Arlington, then the call would automatically be routed by the local exchange carrier because row **350** in the LATA Table has the Dial Plan populated with "EMS."

The description of the present invention has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention and the practical application to enable others of ordinary skill in the art to understand the invention for various embodiments with

various modifications as are suited to the particular use contemplated.

CGTES.0143

CLAIMS:

What is claimed

- 1 1. A method for selecting a carrier type for routing a call, said method comprising:
2 determining whether a called party is inside a local calling scope of a calling
3 party;
4 responsive to a determination that said called party is inside a local calling scope
5 of said calling party, selecting a first carrier as said carrier type;
6 responsive to a determination that said called party is outside said local calling
7 scope of said calling party, selecting a second carrier as said carrier type if an originating
8 LATA of said calling party and a terminating LATA of said called party are the same and
9 selecting a third carrier as said carrier type if said originating LATA and said terminating
10 LATA are different.
- 1 2. The method of claim 1 wherein said step of determining whether a called party is
2 inside said local calling scope of a calling party comprises:
3 determining an originating rate center and a terminating rate center by performing
4 a lookup in a LATA table using a calling party number and a called party number; and
5 searching for said terminating rate center in an originating rate center table.
- 1 3. The method of claim 2 wherein if said terminating rate center is found in said
2 originating rate center table and an extended dial plan entry in said table is null for said
3 terminating rate center, said called party is inside said local calling scope.
- 1 4. The method of claim 3 wherein if said terminating rate center is found in said
2 originating rate center table and said extended dial plan entry in said table indicates that
3 an extended dial plan is required for said terminating rate center, said called party is
4 inside said local calling scope only if either said called party or said calling party

5 subscribes to said extended dial plan.

1 5. The method of claim 2 wherein said lookup is performed using a key chosen from
2 the group consisting of a NPA-NXX-X combination and a NPA-NXX combination.

1 6. The method of claim 2 wherein said lookup of said originating rate center is
2 performed using said calling party number and wherein said lookup of said terminating
3 rate center is performed using said called party number.

1 7. The method of claim 1 wherein said determination that said called party is inside
2 said local calling scope of said calling party is made when said terminating rate center is
3 found in an originating rate center table for said originating rate center.

1 8. The method of claim 1 wherein said determination that said called party is inside
2 said local calling scope of said calling party is made when said terminating rate center is
3 found in an originating rate center table for said originating rate center and an extended
4 dial plan requirement indicated in said originating rate center table for said terminating
5 rate center is satisfied.

1 9. The method of claim 1 wherein said originating LATA and said terminating
2 LATA are the same when a lookup in a LATA table using a calling party number and a
3 called party number indicates that an originating LATA key and a terminating LATA key
4 are equal.

1 10. The method of claim 1 further comprising:
 2 comparing an originating NPA-NXX to a terminating NPA-NXX prior to
 3 determining whether a called party is inside a local calling scope of a calling party; and
 4 responsive to a determination that said originating NPA-NXX and said
 5 terminating NPA-NXX are the same, selecting a local exchange carrier as said carrier
 6 type.

1 11. A method for determining a carrier type for routing a call, said method
 2 comprising:
 3 comparing an originating NPA-NXX to a terminating NPA-NXX;
 4 responsive to a determination that said originating NPA-NXX and said
 5 terminating NPA-NXX are the same, selecting a local exchange carrier as said carrier
 6 type;
 7 responsive to a determination that said originating NPA-NXX and said
 8 terminating NPA-NXX are different, determining an originating rate center for a calling
 9 party and a terminating rate center for a called party;
 10 responsive to a determination that said terminating rate center and said originating
 11 rate center are the same, selecting a local exchange carrier as said carrier type;
 12 responsive to a determination that said terminating rate center and said originating
 13 rate center are different, searching an originating rate center table for said terminating rate
 14 center;
 15 responsive to finding said terminating rate center in said originating rate center
 16 table, determining whether said terminating rate center requires an extended dial plan to
 17 make a local call from said originating rate center to said terminating rate center;
 18 responsive to a determination that said extended dial plan is required, selecting
 19 said local exchange carrier as said carrier type if either said calling party or said called
 20 party subscribe to said dial plan, and if neither said calling party nor said called party

21 subscribe to said dial plan, selecting an IntraLATA carrier as said carrier type if an
 22 originating LATA is the same as a terminating LATA and selecting an InterLATA carrier
 23 if said originating LATA is different from said terminating LATA;
 24 responsive to a determination that said extended dial plan is not required,
 25 selecting a local exchange carrier as said carrier type; and
 26 responsive to not finding said terminating rate center in said originating rate
 27 center table, selecting said IntraLATA carrier as said carrier type if said originating
 28 LATA is the same as said terminating LATA and selecting said InterLATA carrier as said
 29 carrier type if said originating LATA is different from said terminating LATA.

1 12. A data processing system for selecting a carrier type for routing a call comprising:
 2 means for determining whether a called party is inside a local calling scope of a
 3 calling party;
 4 means, responsive to a determination that said called party is inside a local calling
 5 scope of said calling party, for selecting a first carrier as said carrier type;
 6 means, responsive to a determination that said called party is outside said local
 7 calling scope of said calling party, for selecting a second carrier as said carrier type if an
 8 originating LATA of said calling party and a terminating LATA of said called party are
 9 the same and selecting a third carrier as said carrier type if said originating LATA and
 10 said terminating LATA are different.

1 13. The data processing system of claim 12 wherein said means for determining
 2 whether a called party is inside said local calling scope of a calling party comprises:
 3 means for determining an originating rate center and a terminating rate center by
 4 performing a lookup in a LATA table using a calling party number and a called party
 5 number; and
 6 means for searching for said terminating rate center in an originating rate center

7 table.

1 14. The data processing system of claim 13 wherein if said terminating rate center is
2 found in said originating rate center table and an extended dial plan entry in said table is
3 null for said terminating rate center, said called party is inside said local calling scope.

1 15. The data processing system of claim 14 wherein if said terminating rate center is
2 found in said originating rate center table and said extended dial plan entry in said table
3 indicates that an extended dial plan is required for said terminating rate center, said called
4 party is inside said local calling scope only if either said called party or said calling party
5 subscribes to said extended dial plan.

1 16. The data processing system of claim 13 wherein said lookup is performed using a
2 key chosen from the group consisting of a NPA-NXX-X combination and a NPA-NXX
3 combination.

1 17. The data processing system of claim 13 wherein said lookup of said originating
2 rate center is performed using said calling party number and wherein said lookup of said
3 terminating rate center is performed using said called party number.

1 18. The data processing system of claim 12 wherein said determination that said
2 called party is inside said local calling scope of said calling party is made when said
3 terminating rate center is found in an originating rate center table for said originating rate
4 center.

1 19. The data processing system of claim 12 wherein said determination that said
2 called party is inside said local calling scope of said calling party is made when said

3 terminating rate center is found in an originating rate center table for said originating rate
4 center and an extended dial plan requirement indicated in said originating rate center table
5 for said terminating rate center is satisfied.

1 20. The data processing system of claim 12 wherein said originating LATA and said
2 terminating LATA are the same when a lookup in a LATA table using a calling party
3 number and a called party number indicates that an originating LATA key and a
4 terminating LATA key are equal.

1 21. The data processing system of claim 12 further comprising:
2 means for comparing an originating NPA-NXX to a terminating NPA-NXX prior
3 to determining whether a called party is inside a local calling scope of a calling party; and
4 means, responsive to a determination that said originating NPA-NXX and said
5 terminating NPA-NXX are the same, for selecting a local exchange carrier as said carrier
6 type.

1 22. A computer program product in a computer readable medium for selecting a
2 carrier type for routing a call, said computer program product comprising:
3 first instructions for determining whether a called party is inside a local calling
4 scope of a calling party;
5 second instructions, responsive to a determination that said called party is inside a
6 local calling scope of said calling party, for selecting a first carrier as said carrier type;
7 third instructions, responsive to a determination that said called party is outside
8 said local calling scope of said calling party, for selecting a second carrier as said carrier
9 type if an originating LATA of said calling party and a terminating LATA of said called
10 party are the same and selecting a third carrier as said carrier type if said originating
11 LATA and said terminating LATA are different.

1 23. The computer program product of claim 22 wherein said first instructions
2 comprises:
3 instructions for determining an originating rate center and a terminating rate
4 center by performing a lookup in a LATA table using a calling party number and a called
5 party number; and
6 instructions for searching for said terminating rate center in an originating rate
7 center table.

1 24. A computer program product in a computer readable medium for determining a
 2 carrier type for routing a call, said computer program product comprising:
 3 first instructions for comparing an originating NPA-NXX to a terminating NPA-
 4 NXX;
 5 second instructions, responsive to a determination that said originating NPA-NXX
 6 and said terminating NPA-NXX are the same, for selecting a local exchange carrier as
 7 said carrier type;
 8 third instructions, responsive to a determination that said originating NPA-NXX
 9 and said terminating NPA-NXX are different, for determining an originating rate center
 10 for a calling party and a terminating rate center for a called party;
 11 fourth instructions, responsive to a determination that said terminating rate center
 12 and said originating rate center are the same, for selecting a local exchange carrier as said
 13 carrier type;
 14 fifth instructions, responsive to a determination that said terminating rate center
 15 and said originating rate center are different, for searching an originating rate center table
 16 for said terminating rate center;
 17 sixth instructions, responsive to finding said terminating rate center in said
 18 originating rate center table, for determining whether said terminating rate center requires
 19 an extended dial plan to make a local call from said originating rate center to said
 20 terminating rate center;
 21 seventh instructions, responsive to a determination that said extended dial plan is
 22 required, for selecting said local exchange carrier as said carrier type if either said calling
 23 party or said called party subscribe to said dial plan, and if neither said calling party nor
 24 said called party subscribe to said dial plan, selecting an IntraLATA carrier as said carrier
 25 type if an originating LATA is the same as a terminating LATA and selecting an
 26 InterLATA carrier if said originating LATA is different from said terminating LATA;

27 eighth instructions, responsive to a determination that said extended dial plan is
28 not required, for selecting a local exchange carrier as said carrier type; and
29 ninth instructions, responsive to not finding said terminating rate center in said
30 originating rate center table, for selecting said IntraLATA carrier as said carrier type if
31 said originating LATA is the same as said terminating LATA and selecting said
32 InterLATA carrier as said carrier type if said originating LATA is different from said
33 terminating LATA.

007060-4449960

- 1 25. A computer readable medium containing a data structure for storing originating
- 2 rate center data comprising an originating rate center table containing an entry for each of
- 3 a plurality of originating rate centers, each entry containing a LATA key, an originating
- 4 rate center, a terminating rate center associated with said originating rate center, and a
- 5 dial plan associated with said terminating rate center.

- 1 26. A computer readable medium containing a data structure for storing rate center
- 2 data comprising a table containing an entry for each of a plurality of NPA-NXX
- 3 combinations, each entry containing a LATA key, a rate center associated with said NPA-
- 4 NXX combination, and a dial plan associated with said NPA-NXX combination.

CGTES.0143

**METHOD AND APPARATUS FOR DETERMINING THE
CARRIER USED FOR AN AIN CALL**

ABSTRACT OF THE DISCLOSURE

5

The present invention provides a method for determining the carrier that should be used for a particular AIN call. The following information is derived for each call: the originating calling party number, the terminating called party number, the originating LATA, the terminating LATA. Using these components, pre-defined tables are accessed
10 that contain local calling plan information. These tables contain rate center and dial plan information that provides the local calling scope that is available to the originator of the call. Based on the information contained in the tables, the appropriate type of carrier for the call is selected and the call is routed using this carrier.





FIGURE 1
CGTES.0143
Continued on Page 2

FIGURE 2
CGTES.0143



LATA TABLE

	305	310	315	320	330	335
	LATA (key)	NPA-NXX Or NPA-NXX-X (key)	Rate Center	Dial Plan	COC	OCN
	552	817244	FORTWORTH		EOC	9533
	552	817245	FORTWORTH		EOC	9533
	552	817246	FORTWORTH		EOC	9533
	552	817247	ARLINGTON		PMC	6010
	552	817249	FORTWORTH		EOC	9533
340	552	817251	GRAPEVINE		EOC	4344
	552	817252	FORTWORTH		EOC	9533
	552	817253	GLENDALE		PMC	6671
	552	817255	FORTWORTH		EOC	9533
	552	817256	FORTWORTH		EOC	8516
	552	817257	FORTWORTH		EOC	9533
	552	817258	FORTWORTH		EOC	9533
	552	817259	ARLINGTON		EOC	7715
	552	817260	ARLINGTON		EOC	7715
	552	817261	ARLINGTON	EMS	EOC	9533
	552	817262	ARLINGTON	EMS	EOC	9533
325	552	817263	FORTWORTH		EOC	9533
	552	817264	ARLINGTON	EMS	EOC	9533
	552	817265	ARLINGTON	EMS	EOC	9533
	552	817266	GLENDALE		PMC	6671
	552	817267	EULESS	EMS	EOC	9533
	552	817268	EULESS	EMS	EOC	9533
	552	817269	GLENDALE		PMC	6671
	552	817270	AZLE		EOC	4344
	552	817271	ARLINGTON		PMC	6010
350	552	817272	ARLINGTON	EMS	EOC	9533
	552	817273	ARLINGTON	EMS	EOC	9533
	552	817274	ARLINGTON		EOC	9533
	552	817275	ARLINGTON		EOC	9533
	552	817276	ARLINGTON		EOC	9533
	552	817277	ARLINGTON		EOC	9533
	552	817278	FORTWORTH		EOC	9533
	552	817279	GRANBURY	EMS	EOC	9533
	552	817280	EULESS		EOC	9533
	552	817281	NRICHLHLS		EOC	9533
	552	817282	EULESS		EOC	9533
	552	817283	EULESS		EOC	9533
	552	817284	ATLAS		EOC	9533
	552	817285	EULESS		EOC	9533
	552	817287	ARLINGTON		EOC	7263
	552	817288	FORTWORTH		EOC	7263
	552	817291	ARLINGTON		PMC	6010
	552	817292	FORTWORTH		EOC	9533
	552	817293	FORTWORTH		EOC	9533
	552	817294	FORTWORTH		EOC	9533
	552	817295	FORTWORTH		EOC	9533
	552	817296	ARLINGTON		PMC	6010
	552	817297	FORTWORTH		EOC	9533
	552	817300	ARLINGTON		PMC	6664
	552	817301	ARLINGTON		EOC	7670
	552	817302	FORTWORTH		EOC	7249
	552	817304	WEATHERFD		PMC	6010
	552	817305	GRAPEVINE		EOC	7758
345	552	817306	FORTWORTH		EOC	9533
	552	817307	ARLINGTON		PMC	6010
	552	817308	ARLINGTON		PMC	6010

FIGURE 3
CGTES.0143

ORIGINATING RATE CENTER TABLE

405 LATA (key)	410 Originating Rate Center (key)	415 Terminating Rate Center	420 Dial Plan	Optional Plan 1	Optional Plan 2	Optional Plan 3	Optional Plan 4
552	DLFTWTARPT	WEATHERFORD	EMS				
552	GRAPEVINE	ALLEN					
552	GRAPEVINE	ALVARADO	EMS				
552	GRAPEVINE	ARGYLE	EMS				
552	GRAPEVINE	ARLINGTON	EMS				
552	GRAPEVINE	AZLE					
552	GRAPEVINE	CADDOMILLS					
552	GRAPEVINE	CARROLLTON					
552	GRAPEVINE	CEDAR HILL	EMS				
552	GRAPEVINE	CLEBURNE	EMS				
552	GRAPEVINE	DALLAS					
552	GRAPEVINE	DENTON	EMS				
552	GRAPEVINE	DESOTO					
552	GRAPEVINE	DLFTWTARPT					
552	GRAPEVINE	EULESS	EMS				
552	GRAPEVINE	FT WORTH					
552	GRAPEVINE	GRANBURY	EMS				
552	GRAPEVINE	GRANDPRARI	EMS				
552	GRAPEVINE	IRVING	EMS				
552	GRAPEVINE	JUSTIN	EMS				
552	GRAPEVINE	KELLER					
552	GRAPEVINE	KENNEDALE	EMS				
552	GRAPEVINE	LEWISVILLE	EMS				
552	GRAPEVINE	MANSFIELD					
552	GRAPEVINE	N RICHLAND HILLS	EMS				
552	GRAPEVINE	PLANO	EMS				
552	GRAPEVINE	RENO	EMS				
552	GRAPEVINE	ROANOKE					
552	GRAPEVINE	ROCKWALL					
552	GRAPEVINE	SEAGOVILLE					
552	GRAPEVINE	SPRINGTOWN	EMS				
552	GRAPEVINE	WEATHERFORD	EMS				
552	IRVING	ALLEN					

FIGURE 4
CGTES.0143

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**Applicants:** Stephen Paul Brennan and James Ralph Bradford**Serial No.:****Filing Date:** August 31, 2000**Title:** Method and Apparatus for Determining the Carrier Used for an AIN Call**Docket No.:** CGTES.0143

DECLARATION AND POWER OF ATTORNEY

As the below named joint inventors, we hereby declare that:

Our residence, post office address and citizenship are as stated below next to our names.

We believe we are the original inventors of the subject matter which is claimed and for which a patent is sought on the invention, design or discovery entitled:

**Method and Apparatus for Determining The
Carrier Used For An AIN Call**

the specification of which is identified above.

We have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above;

We acknowledge the duty to disclose to the Office all information known to us to be material to the patentability of this application as defined by Title 37, Code of Federal Regulations, § 1.56.

We hereby claim no foreign priority benefits under 35 U.S.C. § 119 of any foreign application(s) for patent or inventor's certificate.

We hereby claim no benefit under 35 U.S.C. § 120 of any United States application for patent

We acknowledge the duty to disclose to the Office all information known to us to be material to patentability as defined in § 1.56 which became available between the filing date of any prior application(s) and the national or PCT international filing date of this application.

We hereby **appoint:**

Leonard Charles Suchyta

Registration No. 25,707

our attorney with full power of substitution and revocation, to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith, and to file and prosecute any international patent applications filed thereon before any international authorities under the Patent Cooperation Treaty.

Send correspondence to: **Leonard Charles Suchyta**
GTE Service Corporation
600 Hidden Ridge, HQE03G13
Irving, TX 75038-3809

Direct telephone calls to: **Leonard Charles Suchyta**
972.718.4741

Attorney Docket No.: **CGTES.0143**

We hereby declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under § 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full name of Sole or First Inventor: **Stephen Paul Brennan**

Inventor's Signature: _____ Date: _____

Residence: **1209 Shannon Lane**
Bedford, Texas 76022

Citizenship: **USA**

Full name of Second Inventor: **James Ralph Bradford**

Inventor's Signature: _____ Date: _____

Residence: **8921 Donna Lu Drive**
Odessa, Florida 33556

Citizenship: **USA**

007060-444960